

The Paragraph beginning at Page 18, lines 13-20, is to be amended as follows:

Further still, as also shown in Figs. 22C and 22E, the (upper) lug 92 of the support 91 has an inner surface 92a which is also slightly angled from the normal of the plane of the support 91 in a direction away from the support 91. As shown in ~~Figs. 17B and 17C~~ Fig. 17B, the upper lugs 92 are formed as resilient members which are able to hinge with respect to the support 91 with a spring-like action. Consequently, when mounted to the casing 20, a slight force is exerted against the lug 27a of the uppermost face 27 of the support frame 22 which assists in securing the support 91 to the support frame 22 of the casing 20 by biasing the (lower) lug 92 into the recess formed between the lower part of the inner surface 25 and the lug 28a of the arm portion 28 of the support frame 22.

The Paragraph beginning at Page 22, lines 13-20, is to be amended as follows:

This is facilitated by using a support member 112 as shown in Fig. 33A, which has a raised portion 112a and a recessed portion 112b at one edge thereof which is arranged to align with the raised and recessed portions 91a and 91b, respectively, of the end PCB support 91 (see Fig. 24). The support member 112 is attached to the rear surface of the end PCB support 91 by engaging a tab 112c with a slot region 91c on the rear surface of the end PCB support 91 (see ~~Figs. 17B and 17C~~ Fig. 17B), and the region 115c of the connector arrangement 115 is retained at upper and lower side surfaces thereof by clip portions 112d of the support member 112 so as that the connection regions of the region 115c are in substantially the same plane as the edge contacting regions on the underside of the end PCB 90.

33

The Paragraph beginning at Page 32, lines 32-39, through to Page 33, lines 1-13, is to be amended as follows:

Exemplary nozzle arrangements which are suitable for the printhead assembly of the present invention are described in the Applicant's following co-pending and granted applications:

U.S. Patent Nos. 6,188,415; 6,209,989; 6,213,588; 6,213,589; 6,217,153; 6,220,694; 6,227,652; 6,227,653; 6,227,654; 6,231,163; 6,234,609; 6,234,610; 6,234,611; 6,238,040; 6,338,547; 6,239,821; 6,241,342; 6,243,113; 6,244,691; 6,247,790; 6,247,791; 6,247,792; 6,247,793; 6,247,794; 6,247,795; 6,247,796; 6,254,220; 6,257,704; 6,257,705; 6,260,953; 6,264,306; 6,264,307; 6,267,469; 6,283,581; 6,283,582; 6,293,653; 6,302,528; 6,312,107; 6,336,710; 6,362,843; 6,390,603; 6,394,581; 6,416,167; 6,416,168; 6,557,977; 6,273,544; 6,299,289; 6,299,290; 6,309,048; 6,378,989; 6,420,196; 6,425,654; 6,439,689; 6,443,558; and 6,634,735, U.S. Patent Application No. ~~6,848,181~~ 09/425,420, U.S. Patent Nos. 6,623,101; 6,406,129; 6,457,809; 6,457,812; 6,505,916; 6,550,895; 6,428,133; 6,305,788; 6,315,399; 6,322,194; 6,322,195; 6,328,425; 6,328,431; 6,338,548; 6,364,453; 6,383,833; 6,390,591; 6,390,605; 6,417,757; 6,425,971; 6,426,014; 6,428,139; 6,428,142; 6,439,693; 6,439,908; 6,457,795; 6,502,306; 6,565,193; 6,588,885; 6,595,624; 6,460,778; 6,464,332; 6,478,406; 6,480,089; 6,540,319; 6,575,549; 6,609,786; 6,609,787; 6,612,110; 6,623,106; 6,629,745; 6,652,071; 6,659,590, U.S. Patent Application Nos. 09/575,127; 09/575,152; U.S. Patent Nos. ~~6,328,417~~ 09/575,176; ~~6,382,779~~ 09/575,177; U.S. Patent Application Nos. 09/608,780; 09/693,079; U.S. Patent Nos. ~~6,854,825~~ 09/693,135; ~~6,684,503~~ 09/693,735; ~~6,672,707~~ 10/129,433;